



7700 Series

5-kVA, DC-enabled
Linear Power Amplifiers

Performance Overview:

- Up to 5000 watts RMS power output
- Small signal response up to 250 kHz
- Up to 60A at 13.5 VDC
- Can be used to create series or parallel systems for up to 3 times the voltage or 4 times the current output.

Features

- Stable when driving highly capacitive loads.
- Field-selectable controlled-voltage or controlled-current operation.
- Can be switched between rail supply modes to optimize for various load impedances.
- Protection circuits guard against over/under voltage, over current, over temperature, and circulating ground currents.

7794

AC Power at 20 kHz: 5000 watts RMS (0.5-ohm load);
50 V_{RMS}, 100A_{RMS}
Small Signal: 28V_{p-p} to 250 kHz
DC Power: 60A at 13.5 VDC
Output Voltage: ±100 V_p

7796

AC Power at 20 kHz: 5000 watts RMS (2-ohm load);
100 V_{RMS}, 50A_{RMS}
Small Signal: 28V_{p-p} to 250 kHz
DC Power: 30A at 28 VDC (13.5 VDC not recommended)
Output Voltage: ±180 V_p

7794 DC Specifications
– High-Current Mode –

VDC	OUTPUT
	1 Hour, 100% Duty Cycle
80	70A
32	115A
28	106A
13.5	60A

7796 X 2 Series System

Typical performance for DO 160 Section 16 testing

		Continuous	In Rush/100 mS
Steady State	115 VAC	60A	140A
Abnormal Surge	180 VAC	40A	100A

AE Techron's **7700-Series** amplifiers offer great power and flexibility. The series consists of two models; each model can be used as a free-standing gain block or combined in multiples to achieve high voltage (300 V_{RMS} at 50 A_{RMS}) or high current (up to 240A at 13.5 VDC continuously).

The 7794 was designed with a very low output impedance and is able to produce up to 60A continuous at 13.5 VDC, making it an excellent battery substitute for transient immunity testing. It is also capable of producing the 80V surges required for DO-160G section 16.6.2.4 abnormal surge testing and is well suited for ISO 7637 pulse 2b and 4 testing.

The 7796, when run in controlled-current mode, is a perfect choice to drive medium to large diameter Helmholtz coils and radiators like those specified in Ford FMC1278 (RI140, RI150).

Features

Features	
Output Impedance	3.2 mΩ + 2.2 μH
Noise Floor	<75 μV
Durable Design	7794 and 7796 amplifiers are built and tested to the most stringent quality standards for long life and outstanding performance
Change from controlled-voltage to controlled-current operation	Field-adjustable control mode and compensation settings
Parallel Operation	Up to four amplifiers can be connected in parallel for added current output
Series Operation	Up to three amplifiers can be connected in series for greater voltage
Ground-lift / Circulating Current Protection	Designed to protect the amplifier, DUT, and signal source from accidental ground loops

Use for testing to these Specifications:

MILITARY

MIL STD 461
RTCA / DO 160

AVIATION

AIRBUS ABD0100
Boeing D6-16050-5
ISO 1540:2006
MIL STD 704

PRODUCT STANDARDS

EN 300329
EN 300340
EN 300342-1
EN 301489-1, -7, -17, -24

AUTOMOTIVE STANDARDS

ISO 7637
ISO 11452-8 and -10
ISO 16750-2
JASO D001-94
SAE J1113-2, -11, -12
SAE J1455

AUTOMOTIVE OEM

BMW 600 13.0 (Part 2)
BMW GS 95004

AUTOMOTIVE OEM (cont.)

BMW GS 95024-2-1
Chrysler CS-11809 (2009)
Chrysler CS-11979
Chrysler DC-11224 Rev.A
DaimlerChrysler DC-10614
DaimlerChrysler DC-10615
DaimlerChrysler DC-11224
DaimlerChrysler PF-10540
EMC-CS-2010JLR V1.1 (2011-01)

Fiat 9.90110
Ford FMC 1278, RI 140
and 150

Ford FMC 1278, CI 210,
230, 250 and 260
Ford ES-XW7T-1A278-AC
Ford WDR 00.00EA
Freightliner 49-00085

GLloyd VI-7-2
GM 9105P

GMW 3097
GMW 3100
GMW 3172

AUTOMOTIVE OEM (cont.)

Honda 3982z-SDA-0030
Hyundai ES 39110-00
Hyundai ES 96100-02
IVECO 16-2103
Kia/Hyundai ES 95400-10
Mack Trucks 606GS15
MAN 3285
Mazda MES PW 67600
MBN 10284-2
Mercedes MBN 10284-2
Mercedes AV EMV
Mercedes-Benz A 211 000 42 99
Mercedes MBN 22100-2
Mitsubishi ES-X82010
MW 3097
Nissan 28400 NDS 02, 03, 05, 07
Nissan 28401 NDS 02
Piaggio 7431
Porsche
PSA B21 7090 & 7110
PSA B21 7110
Renault 36.00.400/B & C

AUTOMOTIVE OEM (cont.)

Renault 36.00.808/--D, E.F, G,
H, J, K, and L
SA B21 7110
Scania TB1400
Scania TB1700
Smart DE1005B
Tata TST/TS/WI/257
Toyota TSC3500G
Toyota TSC3590G
Toyota TSC6203G
Toyota TSC7001G
Toyota TSC7034G
UN ECE R10 (Automotive)
Volvo STD 515-0003
Volvo EMC Requirements
VW TL 801 01
VW TL 820 66
VW TL 821 66
VW TL 823 66
VW TL 824 66
VW TL 825 66

AE Techron Sales Representative